DuPont Packaging & Industrial Polymers





Fusabond® resins Product Data Sheet

				-0		
11	es	cri	m	11	$\boldsymbol{\cap}$	
u	-3	uli	u	ш	u	ш

Product Description DuPont™ Fusabond® C250 is a modified ethylene vinyl acetate copolymer.

Fusabond C250 is a grade with a higher level of anhydride modification, and is mainly intended for use as a component in a blend with other polyolefin resins. It is not intended for extrusion in its pure form in typical extrusions or coextrusions.

Restrictions

Material Status

Commercial: Active

Typical Characteristics

Applications

Adhesion promoter and coupling agent.

Typical Properties

Physical	Nominal Values	Test Met	Test Method(s)		
* Density ()	0.962 g/cm ³	ASTM D792	ISO 1183		
* Melt Flow Rate (190°C/2.16kg)	1.4 g/10 min	ASTM D1238	IS0 1133		
Thermal	Nominal Values	Test Meti	Test Method(s)		
Melting Point (DSC)	71°C (160°F)	ASTM D3418	ISO 3146		
Freezing Point (DSC)	51°C (124°F)	ASTM D3418	ISO 3146		

Processing Information

General

* Maximum Processing Temperature 230°C (446°F)

FDA Status Information

Fusabond® C250 resin complies with Food and Drug Administration Regulation 21 CFR 175.105 - - Adhesives. This Regulation describes adhesives that may be used as components of articles intended for use in packaging, transporting, or holding food, subject to the limitations and requirements therein.

The information and certifications provided herein are based on data we believe to be reliable, to the best of our knowledge. The information and certifications apply only to the specific material designated herein as sold by DuPont and do not apply to use in any process or in combination with any other material. They are provided at the request of and without charge to our customers. Accordingly, DuPont cannot guarantee or warrant such certifications or information and assumes no liability for their use.

Regulatory Information

For information on regulatory compliance outside the U.S., consult your local DuPont representative.

Safety & Handling

For information on appropriate Handling & Storage of this polymeric resin, please refer to the Material Safety Data Sheet..

A Product Safety Bulletin, Material Safety Data Sheet, and/or more detailed information on extrusion processing and/or compounding of this polymeric resin for specific applications are available from your DuPont Packaging and Industrial Polymers representative.

Read and Understand the Material Safety Data Sheet (MSDS) before using this product

Regional Centres

DuPont operates in more than 70 countries. For help finding a local representative, please contact one of the following regional customer contact centers:

Americas

DuPont Company Chestnut Run Plaza – Bldg. 730 974 Centre Road Wilmington, Delaware 19805 U.S.A. Toll-Free (USA): 1-800-628-6208 Telephone: 1-302-774-1000

Fax: 1-302-355-4013

DuPont do Brasil, S.A. Alameda Itapecuru, 506 06454-080 Barueri, SP Brasil Telephone: +55 11 4166 8000 Fax: +55 11 4166 8736

Asia Pacific

DuPont China Holding Co., Ltd. Shanghai Branch 399 Keyuan Road, Bldg. 11 Zhangjiang Hi-Tech Park Pudong New District, Shanghai P.R. China (Postcode: 201203) Telephone +86 21 3862 2888 Fax +86-21-3862-2889

Europe / Middle East / Africa

DuPont de Nemours Int'1. S.A. 2,Chemin du Pavillon Box 50 CH-1218 Le Grand Saconnex Geneva, Switzerland Telephone +41 22 717 51 11 Fax +41 22 717 55 00

http://fusabond.dupont.com

The data listed here fall within the normal range of properties, but they should not be used to establish specification limits nor used alone as the basis of design. The DuPont Company assumes no obligations or liability for any advice furnished or for any results obtained with respect to this information. All such advice is given and accepted at the buyer's risk. The disclosure of information herein is not a licence to operate under, or a recommendation to infringe, any patent of DuPont or others. Since DuPont cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information.

CAUTION: Do not use DuPont materials in medical applications involving implantations in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medicalk applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of DuPont POLICY Regarding Medical Applications H-50103-3 and DuPont CAUTION Regarding Medical Applications H-50102-3.

Copyright © 2009 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and trademarks designated with "®" are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

This data sheet is effective as of 05/13/2008 06:32:50 PM and supersedes all previous versions.