

## NORDEL<sup>™</sup> IP 4570 Hydrocarbon Rubber

## **Overview**

NORDEL<sup>™</sup> IP 4570 Hydrocarbon Rubber is an amorphous ethylene-propylene-diene terpolymer (EPDM) grade designed for extruded applications. It is ideally suited for dense extruded profiles, coolant hoses, and general-purpose moldings. The combination of high viscosity and low crystallinity allows for good balance of processability, extensibility, low-temperature properties, and performance.

Main Characteristics:

- Amorphous
- Medium diene
- · High molecular weight
- · Good low temperature properties
- · Complies with

U.S. FDA 21 CFR 177.2600,

U.S. FDA 21 CFR 177.1520 (See NOTES 1),

U.S. FDA 21 CFR 175.105 (See NOTES 2),

U.S. FDA 21 CFR 177.1210.

Consult the regulations for complete details.

Applications:

- · Extruded profiles
- Coolant hoses

## NOTES:

(1) Can be used in contact with all foods except water in oil emulsions, high or low fat, and low moisture fats and oil.(2) Adhesives only.

| Physical                                 | Nominal Value | (English) | Nominal Value | (SI)  | Test Method |
|--|---------------|-----------|---------------|-------|-------------|
| Density                                  | 0.860         | g/cm³     | 0.860         | g/cm³ | ASTM D297   |
| Ethylene Content                         | 50.0          | wt%       | 50.0          | wt%   | ASTM D3900  |
| Ethylidene Norbornene (ENB) Content      | 5.0           | wt%       | 5.0           | wt%   | ASTM D6047  |
| Mooney Viscosity (ML 1+4, 257°F (125°C)) | 70            | MU        | 70            | MU    | ASTM D1646  |
| Ash Content                              | < 0.1         | wt%       | < 0.1         | wt%   | ASTM D296   |
| Molecular Weight Distribution            | Medium        |           | Medium        |       | Dow Method  |
| Propylene Content                        | 45.0          | wt%       | 45.0          | wt%   | ASTM D3900  |
| Residual Transition Metal                | < 10          | ppm       | < 10          | ppm   | Dow Method  |
| Volatile Matter                          | < 0.40        | wt%       | < 0.40        | wt%   | Dow Method  |

Storage and Handling:

The quality of EPDM products may be affected by exposure to artificial or natural light. This product should be stored indoors in its original packaging and out of direct sunlight.

## Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

| Product<br>Stewardship   | The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products – from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.   |   |                              |  |  |  |
|--|--|---|------------------------------|--|--|--|
| Customer<br>Notice   | Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.   |   |                              |  |  |  |
| Medical<br>Applications Policy   | <ul> <li>NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service ("Product") into any commercial or developmental application that is intended for:</li> <li>a. long-term or permanent contact with internal bodily fluids or tissues. "Long-term" is contact which exceeds 72 continuous hours;</li> <li>b. use in cardiac prosthetic devices regardless of the length of time involved ("cardiac prosthetic devices" include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);</li> <li>c. use as a critical component in medical devices that support or sustain human life; or</li> <li>d. use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.</li> </ul> Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS. |   |                              |  |  |  |
| Disclaimer   | NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because<br>use conditions and applicable laws may differ from one location to another and may change with time, the<br>Customer is responsible for determining whether products and the information in this document are<br>appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices<br>are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation<br>or liability for the information in this document. <b>NO WARRANTIES ARE GIVEN; ALL IMPLIED</b><br><b>WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE</b><br><b>EXPRESSLY EXCLUDED</b> .<br>NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined;<br>(2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications  |   |                              |  |  |  |
|  | to supply or otherwise commercializ<br>NOTICE: This data is based of<br>laboratory testing. They are of<br>of Dow products are beyond<br>suitability of these materials a<br>To the best of our knowledge,   | and (4) although Dow may from time to time provide samples of such products, Dow is not obligated<br>cialize such products for any use or application whatsoever.<br>Seed on information Dow believes to be reliable, as demonstrated in controlled<br>ire offered in good faith, but without guarantee, as conditions and method of use<br>ond Dow's control. Dow recommends that the prospective user determine the<br>als and suggestions before adopting them on a commercial scale.<br>dge, the information contained herein is accurate and reliable as of the date of<br>do not assume any liability for the accuracy and completeness of such |                              |  |  |  |
| Additional   | North America  |   | Europe/Middle East           | +800-3694-6367                                   |  |  |
| Information  | U.S. & Canada:   | 1-800-441-4369  |                              | +31-11567-2626                                   |  |  |
|  | Mexico:  | 1-989-832-1426<br>+1-800-441-4369   | Italy:                       | +800-783-825                                     |  |  |
|  | Latin America<br>Argentina:<br>Brazil:<br>Colombia:<br>Mexico:   | +54-11-4319-0100<br>+55-11-5188-9000<br>+57-1-219-6000<br>+52-55-5201-4700  | South Africa<br>Asia Pacific | +800-99-5078<br>+800-7776-7776<br>+603-7965-5392 |  |  |
| www.dowplastics.com  | This document is intended for use within Asia Pacific, Europe, Latin America, North America  |   |                              |  |  |  |
| and a second sec | Published: 2005-05-05  |   |                              |  |  |  |
|  |  |   |                              |  |  |  |
|  | © 2017 The Dow Chemical C  | ompany  |                              |  |  |  |

